

**K-Resin® KR53 Styrene-Butadiene Copolymer**

Version 1.2

Revision Date 2011-01-25

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**Product information**

Trade name : K-Resin® KR53 Styrene-Butadiene Copolymer
Material : 1107021, 1107035, 1107026, 1107020, 1107025, 1107034,
1106647, 1106646, 1106644

Company : Chevron Phillips Chemical Company LP
K-Resin® Styrene Butadiene Copolymer
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Brusselsesteenweg 355
B-3090 Overijse
Belgium

MSDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:msds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887
Asia: +800 CHEMCALL (+800 2436 2255) China: 0532.8388.9090
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Chemcare Asia: Tel: +65 6848 9048 - Mob: +65 8382 9188 - Fax: +65 6848
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : MSDS@CPChem.com
Website : www.CPChem.com

The manufacturer does not recommend using any K-Resin® SBC grade in medical applications that involve permanent or temporary implantation in the human body.

2. HAZARDS IDENTIFICATION**Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Not a dangerous substance according to Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

Classification (67/548/EEC, 1999/45/EC)

In accordance with Directive 1999/45/EC, the product does not need to be classified nor labeled.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Not a dangerous substance according to Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Special labeling of certain mixtures : Material safety datasheet available on request for professional users.
2-Propenoic acid, 2-[1-[3,5-bis(1,1-dimethylpropyl)-2-hydroxyphenyl]ethyl]-4,6-bis(1,1-dimethylpropyl)phenyl ester

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : KRDEV032

Mixtures**Hazardous ingredients**

Chemical Name	CAS-No. EINECS-No.	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
Styrene-Butadiene Copolymer	9003-55-8			95 - 100

4. FIRST AID MEASURES

If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If symptoms persist, call a physician.

In case of skin contact : If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed : Do not induce vomiting without medical advice.

5. FIRE-FIGHTING MEASURES

Flash point : No data available

Autoignition temperature : No data available

Suitable extinguishing : Water. Water mist. Dry chemical. Carbon dioxide (CO₂). If

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

media	possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer.
Specific hazards during fire fighting	: Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
Special protective equipment for fire-fighters	: Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire and explosion protection	: Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Hazardous decomposition products	: Simple Hydrocarbons. Carbon oxides.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	: Sweep up to prevent slipping hazard. Avoid breathing dust.
Environmental precautions	: Do not contaminate surface water. Prevent product from entering drains.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum.
Additional advice	: Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

7. HANDLING AND STORAGE**Handling**

Advice on safe handling	: Use good housekeeping for safe handling of the product. Keep out of water sources and sewers. Spilled pellets and powders may create a slipping hazard. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient.
Advice on protection against fire and explosion	: Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Storage

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

Requirements for storage areas and containers : Keep in a dry place. Keep in a well-ventilated place.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear a NIOSH approved respirator. Use the following elements for air-purifying respirators: Dusts and Mists. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Dust safety masks are recommended when the dust concentration is excessive.

Eye protection : Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.

Skin and body protection : At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.

Protective measures : .

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties****Appearance**

Form : Pellets

Physical state : Solid

Color : Clear to hazy

Odor : Mild to no odor

Safety data

Flash point : No data available

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

Autoignition temperature : No data available
pH : Not applicable
Vapor pressure : Not applicable
Water solubility : Negligible
Viscosity, kinematic : Not applicable

10. STABILITY AND REACTIVITY

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure

Possibility of hazardous reactions

Conditions to avoid : Avoid prolonged storage at elevated temperature.
Materials to avoid : Avoid contact with strong oxidizing agents.
Thermal decomposition : Simple Hydrocarbons, Carbon oxides

11. TOXICOLOGICAL INFORMATION**K-Resin® KR53 Styrene-Butadiene Copolymer**

Acute oral toxicity : Presumed Not Toxic

K-Resin® KR53 Styrene-Butadiene Copolymer

Acute inhalation toxicity : Presumed Not Toxic

K-Resin® KR53 Styrene-Butadiene Copolymer

Acute dermal toxicity : Presumed Not Toxic

K-Resin® KR53 Styrene-Butadiene Copolymer

Skin irritation : May cause skin irritation and/or dermatitis.

K-Resin® KR53 Styrene-Butadiene Copolymer

Eye irritation : Product dust may be irritating to eyes, skin and respiratory system.

K-Resin® KR53 Styrene-Butadiene Copolymer

Aspiration toxicity : No aspiration toxicity classification.

12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

Elimination information (persistence and degradability)

Bioaccumulation : Does not bioaccumulate.

Mobility : The product is insoluble and floats on water.

Additional
adviceEnvironmental fate
and pathways : No data available

Biodegradability : This material is not expected to be readily biodegradable.

Further information on ecology**Additional ecological
information** : This material is not expected to be harmful to aquatic
organisms.
Fish or birds may eat pellets which may obstruct their
digestive tracts.**13. DISPOSAL CONSIDERATIONS**

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.**14. TRANSPORT INFORMATION****The shipping descriptions shown here are for bulk shipments only, and may not apply to
shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

USDOTNOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
TRANSPORTATION BY THIS AGENCY.**IMO / IMDG**NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
TRANSPORTATION BY THIS AGENCY.

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

IATA

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

15. REGULATORY INFORMATION**National legislation**


Major Accident Hazard : 96/82/EC Update: 2003
 Legislation Directive 96/82/EC does not apply

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
 United States of America US.TSCA : On the inventory, or in compliance with the inventory
 Canada NDSL : On the inventory, or in compliance with the inventory
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : Not in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

NFPA Classification : Health Hazard: 0
 Fire Hazard: 1
 Reactivity Hazard: 0

**Further information**

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control

K-Resin® KR53 Styrene-Butadiene Copolymer

Version 1.2

Revision Date 2011-01-25

and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LOAEL	Lowest Observed Adverse Effect Level
AICS	Australia, Inventory of Chemical Substances	NFPA	National Fire Protection Agency
DSL	Canada, Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
NDSL	Canada, Non-Domestic Substances List	NTP	National Toxicology Program
CNS	Central Nervous System	NZIoC	New Zealand Inventory of Chemicals
CAS	Chemical Abstract Service	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration	NOEC	No Observed Effect Concentration
EC50	Effective Concentration 50%	OSHA	Occupational Safety & Health Administration
EINECS	European Inventory of Existing Chemical Substances	PEL	Permissible Exposure Limit
MAK	Germany Maximum Concentration Values	PICCS	Philippines Inventory of Commercial Chemical Substances
GHS	Globally Harmonized System	PRNT	Presumed Not Toxic
>=	Greater Than or Equal To	RCRA	Resource Conservation Recovery Act
IC50	Inhibition Concentration 50%	STEL	Short-term Exposure Limit
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act.
IECSC	Inventory of Existing Chemical Substances in China	TLV	Threshold Limit Value
ENCS	Japan, Inventory of Existing and New Chemical Substances	TWA	Time Weighted Average
KECI	Korea, Existing Chemical Inventory	TSCA	Toxic Substance Control Act
<=	Less Than or Equal To	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
LC50	Lethal Concentration 50%	WHMIS	Workplace Hazardous Materials Information System
LD50	Lethal Dose 50%		